
Led-Dimmer Insats

Type: 6523 UR-104-500

EI-Number: 1361055

Product ID: 2CKA006512A0354

GTIN: 4011395344071



LED dimmer With rotary control.

Two-way switch and soft-catch.

With N-terminal.

2- or 3-wire connection (neutral conductor not required).

Neutral conductor optionally connectable (recommended for the connection of low loads < 10 W/VA).

Very low installation depth: < 20 mm Without claws.

Optimised for dimming of retrofit LED lamps (LEDi).

For dimmable Retrofit-LEDs (LEDi).

For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers.

For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps with conventional or electronic transformers and dimmable energy-saving halogen lamps.

Mix operaton of LEDi with conventional loads possible.

With manually adjustable operating mode: trailing / leading edge control.

With adjustable minimum/maximum brightness.

Low-noise level by MOSFET transistors.

With electronic short-circuit protection. With electronic overload protection.

Without cover plate.

Rated voltage: 230 V~, + 10% / - 10% Rated frequency: 50 Hz/60 Hz

Nominal power (L): 2 - 100 W/VA (leading-edge control)

Nominal power (R, C): 10 - 360 W/VA (trailing-edge control)

Nominal power (LEDi): 2 - 100 W/VA (leading-edge control)

Nominal power (LEDi): 2 - 200 W/VA (trailing-edge control)

Technical specification

Classification

Lämplig för skyddsklass (IP):	IP20
-------------------------------	------

ETIM Data

Sammansättning:	Grundelement
Manövreringsmetod:	Vrid-/Tryckknapp
Appstyrning via Bluetooth:	No
Dimning framkant (phase cut-on):	Yes
Dimning bakkant (phase cut-off):	Yes
Trappfunktion*:	No
Typ av last:	Universal och LED Retrofit
Omformare ingång:	No
Ljusvärdesminne:	Yes
Kan användas med knapp:	No
Kan användas med rörelsesensor:	No
Kan användas med närvaroindikator:	No
Kan användas med tidsomkopplare/timer:	No
Kan användas med överföringsknapp:	No
Kan användas med infrarödknapp:	No
Monteringsmetod:	Infällt montage
Typ av fastsättning:	Montering med skruv
Material:	Plast
Materialkvalitet:	Termoplast
Halogenfri:	No
Ytskydd:	Obehandlad
Typ av yta:	Matt
Färg:	Svart
Transparent:	No
Slagtålighet (IK):	IK00
Märkspänning:	230 V

Product Card

Led-Dimmer Insats



Max. växlingseffekt LED:	360 W
Ledararea:	1...2.5 mm ²
Apparatens bredd:	71 mm
Apparatens höjd:	71 mm
Apparatens djup:	42 mm
Minsta djup på infälld installationsdosa:	20 mm
Kompatibel med Apple HomeKit:	No
Kompatibel med Google Assistant:	No
Kompatibel med Amazon Alexa:	No
Med stöd för IFTTT:	No